

We Take Care of your Fruits all Around the World

LOGIKA

Electronic Grader




fruit technology equipment

futura-grading.com

t. +39 (0) 547 632749
e. info@futura-technology.com



FUTURA s.r.l.

Registered Office
Via Paleocapa, 6
20121 Milano - Italy

Operational Headquarter
Via R. Mattioli, 136 - 156
47522 Cesena (FC) - Italy


fruit technology equipment

LOGIKA LATERAL DISCHARGE

Logika Central Discharge is the most suitable grading solution for low production rates. In fact, it offers the possibility to work with two number of lines that can vary from 1 or 2 channels (lanes). The optimal filling rate of our trolleys, which is up to 90-95%, guarantees the most possible production capacity. Like any grading system by Futura, Logika Lateral Discharge caters to a wide range of needs. The flexibility of this line, attention to detail, and the use of high-quality materials ensure top-quality performance and the gentlest handling of your products.



TECHNICAL FEATURES

GRADING METHODS

Weight, Size, Colour and External Quality in some applications.

RANGE OF WORKABLE PRODUCTS

Apple, Pears, All Stone Fruits, Pomegranate, Tropical Fruits, All Citrus, Date, Dragon Fruits, Vegetables, Persimmons & Garlic.

TROLLEY PITCHES: CUP OR ROLLER

Cover a wide range, depends on size of the products: 76mm, 95mm, 114mm, 114+mm, 152mm & 190mm.

NUMBER OF POSSIBLE WORKING LANES

1 or 2 lanes.

WORKING SPEED

Depends on the products from 5 to 15 fruits / sec. / each lane.

STRUCTURE

Extruded aluminium, painted profiles, galvanized iron or Stainless Steel AISI 304.

TYPE OF FRUITS DISCHARGE


Lateral discharge directly to fruits collection tanks, in one side (for single lane) or both sides (for 2 lanes).

INCLUDED ACCESSORIES

Remote diagnostic supports via internet, efficient programming and control system, offering a wide range of statistical reports, recall and Activating of any saved program as you need, setting the outputs and exits based on what you need.

OPTIONAL ACCESSORIES

Labelling system, Traceability system, Automatic trolleys washing system.



WEIGHT DETECTION

Our graders are specifically designed to accurately measure the weight of a wide range of products. They detect the weight of each individual product using high-quality load cells constructed from stainless steel and chrome-plated housings. Our system ensures optimal precision even when operating at the highest speeds.




PRE-ALIGNING SYSTEM

The pre-aligning system consists of V-shaped AISI 304 components, equipped with two distinct speed belts for each channel. Its primary objective is to efficiently align the products prior to their entry into the grading machine.

SINGULATION SYSTEM

The key element of our machines, which plays a crucial role, involves the utilization of metal sheets covered with soft rubber. These specially designed sheets transport the products into the trolleys, ensuring optimal singulation and precise handling of each individual item.



DIAMETER AND COLOUR DETECTION

Our grader utilizes a sophisticated system consisting of a box equipped with LED lighting and high-resolution cameras. This innovative setup enables the detection of the diameter, shape, and colour of each product with remarkable precision. The dedicated cameras for diameter measurement and colour analysis are installed separately for each working lane, ensuring accurate and detailed data collection.



OUTLETS AND PRODUCTS DISCHARGE

The products are seamlessly discharged from the trolleys using computer-controlled solenoids. These solenoids expertly tilt the trolleys, allowing each product to gracefully descend onto an accompanying curtain before smoothly landing on the outfeed belt.

